



Product Service

CERTIFICATE

No. B 071686 0008 Rev. 00

Holder of Certificate: **COLCOM GROUP S.p.A.**
 Via degli Artigiani 56 Int. 1
 25075 NAVE (BS)
 ITALY

Certification Mark:



Product: **Door Fittings
(Hinge)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: MES1078596B00TR

Valid until: 2024-07-31

Date, 2019-08-09

(GIANPAOLO MENSA)



Product Service

CERTIFICATE

No. B 071686 0008 Rev. 00

Model(s):

D100E10, D100E10A, D100E10BTNFA, D100E10BTSF, D100E10L, D100E10NF, D100E10NFA, D100E10NFSF, D100E10SF, D100E10SFA, D100E10XSFG, D101E10, D101E10L, D101E10LNF, D101E10NF, D101E10NFSF, D101E10SF, D101E10SF/110, D101E10XSFG.

Model	Efficiency [%]	Range [°]	Load Max [Kg]	Description
D100E10	90	0°; +180°; -180°	100	Single automatic Hydraulic hinge
D100E10A				Single Biloba body square ground plate
D100E10BTNFA				Unique no brake group for Turkish bath
D100E10BTSF				Single Biloba hinge BT no stop
D100E10L				100E10L Biloba single depotented body
D100E10NF				Unique hinge without brake unit
D100E10NFA				100E10NFA unique hinge no brake and earthing square plate
D100E10NFSF				Unique hinge without brake unit and without stopping
D100E10SF				D100E10SF single Biloba body without stopping
D100E10SFA				D100E10SFA body single Biloba without stopping and square plate



Product Service

CERTIFICATE

No. B 071686 0008 Rev. 00

Model	Efficiency [%]	Range [°]	Load Max [Kg]	Description
D100E10YXSG	90	0°; +180°; -180°	100	MD100E10Y body of unique hinge, without floor plate
D101E10				101E10 single- swivel Biloba body overheading for external use
D101E10L				D101E10L Biloba single body L-shutter for external use
D101E10LNF				101E10LNF body single base Biloba locking device for external use
D101E10NF				101E10NF single body Biloba no brake external use.
D101E10NFSF				101E10NFSF single-swivel Biloba Overheading for external use.
D101E10SF				Single double hinge without stop
D101E10SF/110				Single double hinge without stops with 110 ° (anti-scaring)
D101E10XSG				MD101E10 body of unique hinge -tilting system

Page 3 of 4

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

CERTIFICATE

No. B 071686 0008 Rev. 00

Material:

Model	Materials
BILOBA UNICA 100E10	Alloy 6063; Alloy 6026; Inox AISI 316L; Inox AISI 303

Tested according to: EN 1154:2006

Production 071686

Facility(ies):

[Signature]
Page 4 of 4